

# Legacy/Outback



## SUBARU

### Armrest Extension

#### INSTALLATION INSTRUCTION

PART No. J2010AG000JD, J2010AG000WB

#### 1.Components

No.	Components	Q'ty
1	Armrest Extension	1
2	Installation Instruction	1

#### 2.Tool Required

- 1) Philips Screwdriver.
- 2) Trim removal tool.

#### 3.Precaution

- 1) Review the instructions completely before starting installation.

#### 4. Installation Procedure

Fig.1



##### 1).Remove the upper cover from center console box.

Pull the upper cover open with a trim removal tool placed in the center of the cover and center console as shown in Fig.1.

! Be careful not to break the upper cover

##### 2). Remove the screw behind cover as shown in Fig.2.

! Keep the removed screw for re-use

Fig.2



##### 3). Pull and remove the rear console box cover rearward as shown in Fig.3.

##### 4). Remove the lid by unfastening two attached screws as shown in Fig.4.

Notice --- This lid is, in some cases, mounted with three screws. In that case, please adjust the number of screws utilized to attach the armrest extension to the center console dependent upon the number of mounting holes of the armrest extension.

Fig.3



##### 5). Attach the armrest extension to the console box with previously removed screws .

! Do not over-tighten the screws. Recommended value 1.3 ± .15 Ft lbs


Fig.4



##### 6). Re-install the rear console box cover (Fig.3) and re-install screws removed in step 2 above(Fig.2) and upper cover(Fig.1).

##### 7). Verify that the armrest extension latches to the center console when closed and that the lid can be extended by pushing button as shown in Fig.5.

Fig.5



CAUTION1 : MAXMUM LOAD LIMIT OF ARMREST EXTENSION IS 66Lbs / 30KG  
IN THE VERTICAL DIRECTION.

2: BE CAREFUL TO AVOID FINGER OR HAND  
CAUGHT BY UPPER AND LOWER LID  
WHEN FOLDED.